

6500-7.5KW

Rotary Phase Converter Data Sheet



TEMCo Heavy Duty Rotary Phase Converters provide utility quality three phase power from a single phase power supply. TEMCo's world class products are being used throughout the United States and internationally.

Common Phase Converter Uses:


- Machine Shops
- Woodworking
- Farm Equipment
- Restaurant Equipment
- Petrochemicals
- Home Hobbyist
- Oil Fields
- Irrigation
- High Tech
- Military
- Aerospace
- Hospitals




Phase Converter Features:


6yr Full 6 Year Warranty

HEAVY DUTY Rugged Heavy Duty Rotary Design

 100% Copper Windings
(Energy Efficient, Environmentally Friendly)

 100% American Made

 208-240v or 440-480v Operation

 Quiet Operation, 63db @ 10ft
(No Louder Than Human Conversation)

Specifications:

1-Phase Input Voltage	208-240v or 440-480v	
1-Phase Input Frequency	60 Hz	
3-Phase Output Voltage	= 1-Phase Volts + 5% on L2 (Non-Loaded)	
3-Phase Output Frequency	60 Hz	
3-Phase Output Voltage Balance	± 5%	
3-Phase Output Phase Angle	120°	
Temperature Rating	40° C Ambient Continuous	
Ambient Humidity	<95% (Non-Condensing)	
Maximum Altitude	3,300 ft. Above Sea Level (De-rate 20% if above 3,300 ft.)	
Enclosure	NEMA 1 (Indoor)	
	230v	460v
Maximum Medium Run or Start HP	5 HP	5 HP
Maximum Hard Run or Start HP	3.3 HP	3.3 HP
Maximum Group Load HP	7.5 HP	7.5 HP
Continuous 3-Phase Output Amps	20.7 Amps	10.35 Amps
Peak 3-Phase Output Amps	27.6 Amps	13.8 Amps
Peak kW Output	7.5 kW	7.5 kW
Peak 1-Phase Amps Required	47.8 Amps	23.9 Amps
Approximate 1-Phase Idle Amps	5 Amps	2.5 Amps
1-Phase Breaker Recommended	60 Amps	40 Amps
1-Phase Fuse Recommended	45 Amp Dual-Element Time Delay	20 Amp Dual-Element Time Delay
Recommended 1-Phase Wire Size	6 AWG	10 AWG
Recommended 3-Phase Wire Size	10 AWG	12 AWG

TEMCo – Tower Electric Motor Co.
41484 Christy St. Fremont, CA 94538

Inside USA (800) 613-2290 International (510) 490-2187
www.temcoindustrialpower.com Fax (510) 490-1507